


Plastic-Encapsulate Transistors

TRANSISTOR (PNP)

FEATURES

- High Voltage Application
- Telephone Application
- Complementary to MMBTA43

MARKING: 2D



MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

| Symbol | Parameter | Value | Unit |
|-----------------|---|----------|-----------------------------|
| V_{CBO} | Collector-Base Voltage | -200 | V |
| V_{CEO} | Collector-Emitter Voltage | -200 | V |
| V_{EBO} | Emitter-Base Voltage | -5 | V |
| I_C | Collector Current | -500 | mA |
| P_C | Collector Power Dissipation | 350 | mW |
| $R_{\theta JA}$ | Thermal Resistance From Junction To Ambient | 357 | $^{\circ}\text{C}/\text{W}$ |
| T_j | Junction Temperature | 150 | $^{\circ}\text{C}$ |
| T_{stg} | Storage Temperature | -55~+150 | $^{\circ}\text{C}$ |


ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}\text{C}$ unless otherwise specified)

| Parameter | Symbol | Test conditions | Min | Typ | Max | Unit |
|--------------------------------------|-----------------|---|------|-----|-------|---------------|
| Collector-base breakdown voltage | $V_{(BR)CBO}$ | $I_C=-100\mu\text{A}, I_E=0$ | -200 | | | V |
| Collector-emitter breakdown voltage | $V_{(BR)CEO}$ | $I_C=-1\text{mA}, I_B=0$ | -200 | | | V |
| Emitter-base breakdown voltage | $V_{(BR)EBO}$ | $I_E=-100\mu\text{A}, I_C=0$ | -5 | | | V |
| Collector cut-off current | I_{CBO} | $V_{CB}=-200\text{V}, I_E=0$ | | | -0.25 | μA |
| Collector cut-off current | I_{CEO} | $V_{CE}=-200\text{V}, I_B=0$ | | | -0.25 | μA |
| Emitter cut-off current | I_{EBO} | $V_{EB}=-5\text{V}, I_C=0$ | | | -0.1 | μA |
| DC current gain | $h_{FE(1)}^*$ | $V_{CE}=-10\text{V}, I_C=-10\text{mA}$ | 40 | | | |
| | $h_{FE(2)}^*$ | $V_{CE}=-10\text{V}, I_C=-1\text{mA}$ | 25 | | | |
| | $h_{FE(3)}^*$ | $V_{CE}=-10\text{V}, I_C=-30\text{mA}$ | 25 | | | |
| Collector-emitter saturation voltage | $V_{CE(sat)}^*$ | $I_C=-20\text{mA}, I_B=-2\text{mA}$ | | | -0.5 | V |
| Base-emitter saturation voltage | $V_{BE(sat)}^*$ | $I_C=-20\text{mA}, I_B=-2\text{mA}$ | | | -0.9 | V |
| Transition frequency | f_T | $V_{CE}=-20\text{V}, I_C=-10\text{mA}, f=100\text{MHz}$ | 50 | | | MHz |
| Collector output capacitance | C_{ob} | $V_{CB}=-20\text{V}, I_E=0, f=1\text{MHz}$ | | | 8 | pF |

*Pulse test: pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2.0\%$.


SOT-23 Tape and Reel

SOT-23 Embossed Carrier Tape




| Dimensions are in millimeter | | | | | | | | | | |
|------------------------------|------|------|------|-------|------|------|------|------|------|------|
| Pkg type | A | B | C | d | E | F | P0 | P | P1 | W |
| SOT-23 | 3.15 | 2.77 | 1.22 | Ø1.50 | 1.75 | 3.50 | 4.00 | 4.00 | 2.00 | 8.00 |

SOT-23 Tape Leader and Trailer




SOT-23 Reel



| Dimensions are in millimeter | | | | | | | | |
|------------------------------|---------|-------|-------|--------|--------|-------|------|-------|
| Reel Option | D | D1 | D2 | G | H | I | W1 | W2 |
| 7" Dia | Ø178.00 | 54.40 | 13.00 | R78.00 | R25.60 | R6.50 | 9.50 | 12.30 |

| REEL | Reel Size | Box | Box Size(mm) | Carton | Carton Size(mm) | G.W.(kg) |
|----------|-----------|------------|--------------|-------------|-----------------|----------|
| 3000 pcs | 7 inch | 45,000 pcs | 203×203×195 | 180,000 pcs | 438×438×220 | |



| SYMBOL | MILLIMETER | |
|----------|------------|-------|
| | MIN | MAX |
| A | 0.900 | 1.150 |
| A1 | 0.000 | 0.100 |
| A2 | 0.900 | 1.050 |
| b | 0.300 | 0.500 |
| c | 0.080 | 0.150 |
| D | 2.800 | 3.000 |
| E | 1.200 | 1.400 |
| E1 | 2.250 | 2.550 |
| e | 0.950 TYP | |
| e1 | 1.800 | 2.000 |
| L | 0.550 REF | |
| L1 | 0.300 | 0.500 |
| θ | 0° | 8° |

DISCLAIMER

JHG PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with JHG products. You are solely responsible for

- (1) selecting the appropriate JHG products for your application;
- (2) designing, validating and testing your application;
- (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements.

These resources are subject to change without notice. JHG grants you permission to use these resources only for development of an application that uses the JHG products described in the resource. Other reproduction and display of these resources are prohibited. No license is granted to any other JHG intellectual property right or to any third party intellectual property right. JHG disclaims responsibility for, and you will fully indemnify JHG and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.