

- ★ Green Device Available
- ★ Super Low Gate Charge
- ★ Excellent Cdv/dt effect decline
- ★ Advanced high cell density Trench technology

Product Summary





| BVDSS | RDSON | ID |
|-------|-------|-------|
| -18V | 19mΩ | -7.0A |

Description

The JH20P07D is the high cell density trenched N-ch MOSFETs, which provides excellent RDSON and efficiency for most of the small power switching and load switch applications. The JH20P07D meet the RoHS and Green Product requirement with full function reliability approved.

SOT-23-3L Pin Configurations



Absolute Maximum Ratings

| Symbol | Parameter | Rating | Units |
|----------------------|--|------------|------------|
| V_{DS} | Drain-Source Voltage | -18 | V |
| V_{GS} | Gate-Source Voltage | ± 12 | V |
| $I_D@T_A=25^\circ C$ | Continuous Drain Current, $V_{GS} @ -4.5V^1$ | -7.0 | A |
| $I_D@T_A=70^\circ C$ | Continuous Drain Current, $V_{GS} @ -4.5V^1$ | -4.8 | A |
| I_{DM} | Pulsed Drain Current ² | -18.8 | A |
| $P_D@T_A=25^\circ C$ | Total Power Dissipation ³ | 1.9 | W |
| T_{STG} | Storage Temperature Range | -55 to 150 | $^\circ C$ |
| T_J | Operating Junction Temperature Range | -55 to 150 | $^\circ C$ |

Thermal Data

| Symbol | Parameter | Typ. | Max. | Unit |
|-----------------|--|------|------|--------------|
| $R_{\theta JA}$ | Thermal Resistance Junction-ambient ¹ | --- | 65 | $^\circ C/W$ |
| $R_{\theta JC}$ | Thermal Resistance Junction-Case ¹ | --- | 80 | $^\circ C/W$ |

Electrical Characteristics (T_J=25°C unless otherwise specified)

| Symbol | Parameter | Test Condition | Min. | Typ. | Max. | Units |
|---|---|--|------|------|------|-------|
| Off Characteristic | | | | | | |
| V _{(BR)DSS} | Drain-Source Breakdown Voltage | V _{GS} =0V, I _D = -250μA | -15 | -18 | - | V |
| I _{DSS} | Zero Gate Voltage Drain Current | V _{DS} = -12V, V _{GS} =0V, | - | - | -1 | μA |
| I _{GSS} | Gate to Body Leakage Current | V _{DS} =0V, V _{GS} = ±12V | - | - | ±100 | nA |
| On Characteristics | | | | | | |
| V _{GS(th)} | Gate Threshold Voltage | V _{DS} =V _{GS} , I _D = -250μA | -0.4 | -0.7 | -1.0 | V |
| R _{DS(on)} | Static Drain-Source on-Resistance <small>note2</small> | V _{GS} = -4.5V, I _D = -7A | - | 19 | 27 | mΩ |
| | | V _{GS} = -2.5V, I _D = -5A | - | 26 | 40 | |
| Dynamic Characteristics | | | | | | |
| C _{iss} | Input Capacitance | V _{DS} = -6V, V _{GS} =0V, f=1.0MHz | - | 1300 | - | pF |
| C _{oss} | Output Capacitance | | - | 302 | - | pF |
| C _{rss} | Reverse Transfer Capacitance | | - | 279 | - | pF |
| Q _g | Total Gate Charge | V _{DS} = -6V, I _D = -7A, V _{GS} = -4.5V | - | 19 | - | nC |
| Q _{gs} | Gate-Source Charge | | - | 4 | - | nC |
| Q _{gd} | Gate-Drain("Miller") Charge | | - | 5 | - | nC |
| Switching Characteristics | | | | | | |
| t _{d(on)} | Turn-on Delay Time | V _{DD} = -6V, I _D = -4A, V _{GS} = -4.5V, R _{GEN} =2.5Ω | - | 11 | - | ns |
| t _r | Turn-on Rise Time | | - | 36 | - | ns |
| t _{d(off)} | Turn-off Delay Time | | - | 29 | - | ns |
| t _f | Turn-off Fall Time | | - | 8 | - | ns |
| Drain-Source Diode Characteristics and Maximum Ratings | | | | | | |
| I _S | Maximum Continuous Drain to Source Diode Forward Current | | - | - | -7 | A |
| I _{SM} | Maximum Pulsed Drain to Source Diode Forward Current | | - | - | -28 | A |
| V _{SD} | Drain to Source Diode Forward Voltage | V _{GS} =0V, I _S = -7A | - | -0.8 | -1.2 | V |

Notes:1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature

2. Pulse Test: Pulse Width≤300μs, Duty Cycle≤2%

Typical Performance Characteristics

Figure 1: Output Characteristics




Figure 2: Typical Transfer Characteristics




Figure 3: On-resistance vs. Drain Current




Figure 4: Body Diode Characteristics




Figure 5: Gate Charge Characteristics




Figure 6: Capacitance Characteristics




Figure 7: Normalized Breakdown Voltage vs. Junction Temperature




Figure 8: Normalized on Resistance vs. Junction Temperature




Figure 9: Maximum Safe Operating Area




Figure 10: Maximum Continuous Drain Current vs. Ambient Temperature






Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Ambient




SOT-23-3L Tape and Reel

SOT-23-3L Embossed Carrier Tape




| Dimensions are in millimeter | | | | | | | | | | |
|------------------------------|------|------|------|-------|------|------|------|------|------|------|
| Pkg type | A | B | C | d | E | F | P0 | P | P1 | W |
| SOT-23 | 3.15 | 2.77 | 1.22 | Ø1.50 | 1.75 | 3.50 | 4.00 | 4.00 | 2.00 | 8.00 |

SOT-23-3L Tape Leader and Trailer




SOT-23-3L Reel



| Dimensions are in millimeter | | | | | | | | |
|------------------------------|---------|-------|-------|--------|--------|-------|------|-------|
| Reel Option | D | D1 | D2 | G | H | I | W1 | W2 |
| 7" Dia | Ø178.00 | 54.40 | 13.00 | R78.00 | R25.60 | R6.50 | 9.50 | 12.30 |

| REEL | Reel Size | Box | Box Size(mm) | Carton | Carton Size(mm) | G.W.(kg) |
|----------|-----------|------------|--------------|-------------|-----------------|----------|
| 3000 pcs | 7 inch | 45,000 pcs | 203×203×195 | 180,000 pcs | 438×438×220 | |



| SYMBOL | MILLIMETER | |
|----------|------------|-------|
| | MIN | MAX |
| A | 0.900 | 1.150 |
| A1 | 0.000 | 0.100 |
| A2 | 0.900 | 1.050 |
| b | 0.300 | 0.500 |
| c | 0.080 | 0.150 |
| D | 2.800 | 3.000 |
| E | 1.200 | 1.400 |
| E1 | 2.250 | 2.550 |
| e | 0.950 TYP | |
| e1 | 1.800 | 2.000 |
| L | 0.550 REF | |
| L1 | 0.300 | 0.500 |
| θ | 0° | 8° |

DISCLAIMER

JHG PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with JHG products. You are solely responsible for

- (1) selecting the appropriate JHG products for your application;
- (2) designing, validating and testing your application;
- (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements.

These resources are subject to change without notice. JHG grants you permission to use these resources only for development of an application that uses the JHG products described in the resource. Other reproduction and display of these resources are prohibited. No license is granted to any other JHG intellectual property right or to any third party intellectual property right. JHG disclaims responsibility for, and you will fully indemnify JHG and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.