

- ★ 100% EAS Guaranteed
- ★ Green Device Available
- ★ Super Low Gate Charge
- ★ Excellent CdV/dt effect decline
- ★ Advanced high cell density Trench technology

Product Summary




| BVDSS | RDS(on) | ID |
|-------|---------|------|
| -40V | 31 mΩ | -23A |

Description

The JH25P04 is the high cell density trenched P-ch MOSFETs, which provide excellent RDS(on) and gate charge for most of the synchronous buck converter applications.

The JH25P04 meet the RoHS and Green Product requirement, 100% EAS guaranteed with full function reliability approved.

TO-252 Pin Configuration



Absolute Maximum Ratings (T_C=25°C unless otherwise specified)

| Symbol | Parameter | Max. | Units | |
|-----------------------------------|---|------------------------|-------|---|
| V _{DSS} | Drain-Source Voltage | -40 | V | |
| V _{GSS} | Gate-Source Voltage | ±20 | V | |
| I _D | Continuous Drain Current | T _C = 25°C | -23 | A |
| | | T _C = 100°C | -12 | A |
| I _{DM} | Pulsed Drain Current ^{note1} | -40 | A | |
| E _{AS} | Single Pulsed Avalanche Energy ^{note2} | 27.6 | mJ | |
| P _D | Power Dissipation | T _C = 25°C | 8 | W |
| R _{θJC} | Thermal Resistance, Junction to Case | 18.8 | °C/W | |
| T _J , T _{STG} | Operating and Storage Temperature Range | -55 to +175 | °C | |

Electrical Characteristics (T_J=25°C unless otherwise specified)

| Symbol | Parameter | Test Condition | Min. | Typ. | Max. | Units |
|---|---|---|------|------|------|-------|
| Off Characteristic | | | | | | |
| V _{(BR)DSS} | Drain-Source Breakdown Voltage | V _{GS} =0V, I _D = -250μA | -40 | - | - | V |
| I _{DSS} | Zero Gate Voltage Drain Current | V _{DS} = -40V, V _{GS} =0V | - | - | -1 | μA |
| I _{GSS} | Gate to Body Leakage Current | V _{DS} =0V, V _{GS} = ±20V | - | - | ±100 | nA |
| On Characteristics | | | | | | |
| V _{GS(th)} | Gate Threshold Voltage | V _{DS} =V _{GS} , I _D = -250μA | -1.0 | -1.6 | -2.5 | V |
| R _{DS(on)} | Static Drain-Source on-Resistance <small>note3</small> | V _{GS} = -10V, I _D = -8A | - | 31 | 44 | mΩ |
| | | V _{GS} = -4.5V, I _D = -5A | - | 44 | 60 | |
| Dynamic Characteristics | | | | | | |
| C _{iss} | Input Capacitance | V _{DS} = -20V, V _{GS} =0V, f=1.0MHz | - | 1034 | - | pF |
| C _{oss} | Output Capacitance | | - | 107 | - | pF |
| C _{rss} | Reverse Transfer Capacitance | | - | 79.5 | - | pF |
| Q _g | Total Gate Charge | V _{DS} = -20V, I _D = -5A, V _{GS} = -10V | - | 20 | - | nC |
| Q _{gs} | Gate-Source Charge | | - | 3.5 | - | nC |
| Q _{gd} | Gate-Drain("Miller") Charge | | - | 4.2 | - | nC |
| Switching Characteristics | | | | | | |
| t _{d(on)} | Turn-on Delay Time | V _{DD} = -20V, I _D = -5A, V _{GS} = -10V, R _{GEN} =2.5Ω | - | 8 | - | ns |
| t _r | Turn-on Rise Time | | - | 15 | - | ns |
| t _{d(off)} | Turn-off Delay Time | | - | 23 | - | ns |
| t _f | Turn-off Fall Time | | - | 9 | - | ns |
| Drain-Source Diode Characteristics and Maximum Ratings | | | | | | |
| I _S | Maximum Continuous Drain to Source Diode Forward Current | | - | - | -23 | A |
| I _{SM} | Maximum Pulsed Drain to Source Diode Forward Current | | - | - | -40 | A |
| V _{SD} | Drain to Source Diode Forward Voltage | V _{GS} =0V, I _S = -10A | - | -0.8 | -1.2 | V |
| t _{rr} | Reverse Recovery Time | V _{GS} = 0V, I _S =-5A, di/dt=100A/μs | - | 29 | - | ns |
| Q _{rr} | Reverse Recovery Charge | | - | 20 | - | nC |

Notes:1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature

2. EAS condition: T_J= 25°C, V_{DD}= -20V, V_G= -10V, L=0.5mH, R_G= 25Ω, I_{AS}= -10.5A

3. Pulse Test: Pulse Width≤300μs, Duty Cycle≤2%

Typical Performance Characteristics

Figure 1: Output Characteristics




Figure 2: Typical Transfer Characteristics




Figure 3: On-resistance vs. Drain Current




Figure 4: Body Diode Characteristics




Figure 5: Gate Charge Characteristics




Figure 6: Capacitance Characteristics




Figure 7: Normalized Breakdown Voltage vs. Junction Temperature




Figure 8: Normalized on Resistance vs. Junction Temperature




Figure 9: Maximum Safe Operating Area




Figure 10: Maximum Continuous Drain Current vs. Case Temperature





Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Case



Test Circuit




Figure A. Gate Charge Test Circuit & Waveforms




Figure B. Switching Test Circuit & Waveforms





Figure C. Unclamped Inductive Switching Circuit & Waveforms


TO-252-2L Tape and Reel

TO-252 Embossed Carrier Tape




| Dimensions are in millimeter | | | | | | | | | | |
|------------------------------|------|-------|------|-------|------|------|------|------|------|-------|
| Pkg type | A | B | C | d | E | F | P0 | P | P1 | W |
| TO-252 | 6.90 | 10.50 | 2.70 | Ø1.55 | 1.75 | 7.50 | 4.00 | 8.00 | 2.00 | 16.00 |

TO-252 Tape Leader and Trailer




TO-252 Reel



| Dimensions are in millimeter | | | | | | |
|------------------------------|--------|--------|--------|-------|-------|--------|
| Reel Option | D | D1 | D2 | W1 | W2 | I |
| 13"Dia | 330.00 | 100.00 | Ø21.00 | 16.40 | 21.00 | Ø13.00 |

| REEL | Reel Size | Box | Box Size(mm) | Carton | Carton Size(mm) | G.W.(kg) |
|-----------|-----------|-----------|--------------|------------|-----------------|----------|
| 2,500 pcs | 13inch | 2,500 pcs | 340×336×29 | 25,000 pcs | 353×346×365 | |



| SYMBOL | MILLIMETER | | |
|------------|------------|--------|--------|
| | MIN | Typ. | MAX |
| A | 2.200 | 2.300 | 2.400 |
| A1 | 0.000 | | 0.127 |
| b | 0.640 | 0.690 | 0.740 |
| c (电镀后) | 0.460 | 0.520 | 0.580 |
| D | 6.500 | 6.600 | 6.700 |
| D1 | 5.334 REF | | |
| D2 | 4.826 REF | | |
| D3 | 3.166 REF | | |
| E | 6.000 | 6.100 | 6.200 |
| e | 2.286 TYP | | |
| h | 0.000 | 0.100 | 0.200 |
| L | 9.900 | 10.100 | 10.300 |
| L1 | 2.888 REF | | |
| L2 | 1.400 | 1.550 | 1.700 |
| L3 | 1.600 REF | | |
| L4 | 0.600 | 0.800 | 1.000 |
| ϕ | 1.100 | 1.200 | 1.300 |
| θ | 0° | | 8° |
| θ_1 | 9° TYP | | |
| θ_2 | 9° TYP | | |

DISCLAIMER

JHG PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with JHG products. You are solely responsible for

- (1) selecting the appropriate JHG products for your application;
- (2) designing, validating and testing your application;
- (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements.

These resources are subject to change without notice. JHG grants you permission to use these resources only for development of an application that uses the JHG products described in the resource. Other reproduction and display of these resources are prohibited. No license is granted to any other JHG intellectual property right or to any third party intellectual property right. JHG disclaims responsibility for, and you will fully indemnify JHG and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.