

Features

- Split Gate Trench MOSFET technology
- Excellent package for heat dissipation
- High density cell design for low $R_{DS(ON)}$

Applications



- Battery switching application
- Hard switched and high frequency circuits
- Power management

Product Summary



BVDSS	R _{DS(ON)}	ID
-60V	9.0mΩ	-80A

TO-252 Pin Configuration



Absolute Maximum Ratings ($T_j = 25^\circ\text{C}$ unless otherwise specified):

Symbol	Parameter	Value	Units
V_{DSS}	Drain-to-Source Voltage	-60	V
I_D	Continuous Drain Current	$T_C = 25^\circ\text{C}$	-80
	Continuous Drain Current	$T_C = 100^\circ\text{C}$	-50
I_{DM}^{a1}	Pulsed Drain Current	-320	A
V_{GS}	Gate-to-Source Voltage	± 20	V
P_D	Power Dissipation	110	W
E_{AS}^{a2}	Single pulse avalanche energy	450	mJ
T_J, T_{stg}	Operating Junction and Storage Temperature Range	150, -55 to 150	$^\circ\text{C}$
T_L	Maximum Temperature for Soldering	300	$^\circ\text{C}$

Thermal Characteristics:

Symbol	Parameter	Value	Units
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	1.1	$^\circ\text{C}/\text{W}$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	60	$^\circ\text{C}/\text{W}$

Static Characteristics						
Symbol	Parameter	Test Conditions	Value			Units
			Min.	Typ.	Max.	
V _{DSS}	Drain to Source Breakdown Voltage	V _{GS} =0V, I _D =-250μA	-60	--	--	V
I _{DSS}	Drain to Source Leakage Current	V _{DS} = -60V, V _{GS} = 0V	--	--	1	μA
I _{GSS(F)}	Gate to Source Forward Leakage	V _{GS} =-20V	--	--	100	nA
I _{GSS(R)}	Gate to Source Reverse Leakage	V _{GS} = +20V	--	--	-100	nA
V _{GS(TH)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250μA	-1.3	-1.8	-2.3	V
R _{DS(ON)1}	Drain-to-Source On-Resistance	V _{GS} =-10V, I _D =-20A	--	9.0	11.0	mΩ
R _{DS(ON)2}	Drain-to-Source On-Resistance	V _{GS} =-4.5V, I _D =-15A	--	12.0	16.0	mΩ
g _{FS}	Forward Transconductance	V _{DS} =-5V, I _D =-20A	50	--	--	S

Dynamic Characteristics						
Symbol	Parameter	Test Conditions	Value			Units
			Min.	Typ.	Max.	
C _{iss}	Input Capacitance	V _{GS} =0V	--	3060	--	pF
C _{oss}	Output Capacitance	V _{DS} =-30V	--	620	--	
C _{rss}	Reverse Transfer Capacitance	f=1.0MHz	--	20	--	
R _g	Gate resistance	V _{GS} =0V, V _{DS} Open	--	2.0	--	Ω

Resistive Switching Characteristics						
Symbol	Parameter	Test Conditions	Value			Units
			Min.	Typ.	Max.	
t _{d(ON)}	Turn-on Delay Time	I _D =-20A, R _L =0.75Ω	--	4.5	--	ns
t _r	Rise Time	V _{DS} = -30V	--	2.5	--	
t _{d(OFF)}	Turn-Off Delay Time	V _{GS} = -10V	--	14.5	--	
t _f	Fall Time	R _G = 3Ω	--	3.5	--	
Q _g	Total Gate Charge	V _{GS} =-10V	--	56	--	nC
Q _{gs}	Gate Source Charge	V _{DS} =-30V	--	11	--	
Q _{gd}	Gate Drain Charge	I _D =-20A	--	9	--	

Source-Drain Diode Characteristics						
Symbol	Parameter	Test Conditions	Value			Units
			Min.	Typ.	Max.	
I _S	Diode Forward Current	T _C =25 °C	--	--	-80	A
I _{SM}	Diode Pulse Current		--	--	-320	A
V _{SD}	Diode Forward Voltage	I _S =-6.0A, V _{GS} =0V	--	--	-1.2	V
t _{rr}	Reverse Recovery time	I _S =-20A, V _{DD} =-30V	--	60	--	ns
Q _{rr}	Reverse Recovery Charge	di/dt=100A/μs	--	105	--	nC


a1: Repetitive rating; pulse width limited by maximum junction temperature

a2: V_{DD} =30V, L=0.3mH, R_G =25Ω, Starting T_j=25°C

Characteristics Curve:


Typ. output characteristics

$$I_D = f(V_{DS})$$




Typ. drain-source on resistance

$$R_{DS(on)} = f(I_D)$$




Typ. transfer characteristics

$$I_D = f(V_{GS})$$




Typ. forward transconductance

$$g_{fs} = f(I_D)$$




Drain-source on-state resistance

$$R_{DS(on)} = f(T_j); I_D = -20A; V_{GS} = -10V$$




Typ. capacitances

$$C = f(V_{DS}); V_{GS} = 0V; f = 1MHz$$




Typ. gate charge

$$V_{GS} = f(Q_{gate}); I_D = -20A$$




Drain-source breakdown voltage

$$V_{BR(DSS)} = f(T_j); I_D = -250\mu A$$




Power Dissipation

$$P_{tot}=f(T_c)$$




$$I_D=f(V_{DS})$$




Max. transient thermal impedance

$$Z_{thJC}=f(t_p)$$




TO-252-2L Tape and Reel

TO-252 Embossed Carrier Tape




Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
TO-252	6.90	10.50	2.70	Ø1.55	1.75	7.50	4.00	8.00	2.00	16.00

TO-252 Tape Leader and Trailer




TO-252 Reel



Dimensions are in millimeter						
Reel Option	D	D1	D2	W1	W2	I
13"Dia	330.00	100.00	Ø21.00	16.40	21.00	Ø13.00

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
2,500 pcs	13inch	2,500 pcs	340×336×29	25,000 pcs	353×346×365	



SYMBOL	MILLIMETER		
	MIN	Typ.	MAX
A	2.200	2.300	2.400
A1	0.000		0.127
b	0.640	0.690	0.740
c (电镀后)	0.460	0.520	0.580
D	6.500	6.600	6.700
D1	5.334 REF		
D2	4.826 REF		
D3	3.166 REF		
E	6.000	6.100	6.200
e	2.286 TYP		
h	0.000	0.100	0.200
L	9.900	10.100	10.300
L1	2.888 REF		
L2	1.400	1.550	1.700
L3	1.600 REF		
L4	0.600	0.800	1.000
Φ	1.100	1.200	1.300
θ	0°		8°
θ 1	9° TYP		
θ 2	9° TYP		

DISCLAIMER

JHG PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with JHG products. You are solely responsible for

- (1) selecting the appropriate JHG products for your application;
- (2) designing, validating and testing your application;
- (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements.

These resources are subject to change without notice. JHG grants you permission to use these resources only for development of an application that uses the JHG products described in the resource. Other reproduction and display of these resources are prohibited. No license is granted to any other JHG intellectual property right or to any third party intellectual property right. JHG disclaims responsibility for, and you will fully indemnify JHG and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.